



PRECISION

QUALITY

RELIABILITY



# MARTINI VFFS RANGE

VERTICAL FORM FILL & SEAL



[www.cliftonpackaging.com](http://www.cliftonpackaging.com)

Clifton Packaging Group are specialist suppliers of complete turnkey packaging lines for Vertical Form Fill and Seal Applications.

Our Martini Range can be integrated into your production line along with our wide variety of weighing and filling equipment.

### Optional Extras

- Servo or Pneumatic Horizontal Seal Jaws
- Thermal Transfer Printer
- Label Applicator
- Twin Reel Film Mandrel for Quick Film Change
- Horizontal Jaw with Euroslot
- Picture Card Insertions
- Square Bottom Device
- Static Eliminator
- Stainless Steel ( washable version )
- Impulse Seal Jaws



Direct Servo Film Drive



Built in Film Splice Included in Unwind Frame



Precision Laser Cut Panels



Easy Change Forming Set



Unwind Frame designed to accept Printer



Adjustable Bag Deflators



## MX 600 S PILLOW PACK

Easy to set up, simple to operate  
economic production



Pillow Pack



Gusseted Pack

- Quick release knife, no tools required
- Photo cell for printed registered film
  - Motorised unwind
- Motorised vertical sealer



## MX 600 S QUAD PACK

Produces quality quad or pillow packs  
or square bottom gusseted bags



Pillow Pack



Gusseted Pack



Quad Pack

- As per MX 600 S Pillow Pack
- Easy adjustable quad seal bars
  - Motorised unwind



## SX 600 DOY STYLE

Produces high quality doy style  
stand up pouches



Stand Up Pouch

- As per MX 600 S Pillow Pack
  - Can produce packs with resealable flap + tape

<b>Bag Type</b> Pillow or Gusseted	<b>Bag Type</b> Quad, Pillow or Gusseted	<b>Bag Type</b> Stand UP Pouch
<b>Max Speed</b> 100 Bags per minute	<b>Max Speed</b> 60 Bags per minute	<b>Max Speed</b> 60 Bags per minute
<b>Bag Width</b> 65mm - 290mm	<b>Bag Width</b> 65mm - 280mm	<b>Bag Width</b> 70mm - 180mm
<b>Bag Length</b> 80mm - 340mm	<b>Bag Length</b> 80mm - 330mm	<b>Bag Length</b> 100 - 280mm
<b>Reel Width</b> 150mm - 600mm	<b>Reel Width</b> 150mm - 600mm	<b>Reel Width</b> 150mm - 500mm
<b>Max Reel Diameter</b> 400mm	<b>Max Reel Diameter</b> 400mm	<b>Max Reel Diameter</b> 400mm
<b>Power Supply</b> 3PNE 16 AMP	<b>Power Supply</b> 3PNE 16 AMP	<b>Power Supply</b> 3PNE 16 AMP
<b>Air Consumption</b> 300 / 10.6 (Lts per min/ CFM)	<b>Air Consumption</b> 216 / 7.7 (Lts per min/ CFM)	<b>Air Consumption</b> 150 / 5.3m (Lts per min/ CFM)
<b>Power Consumption</b> 5.0 Kw	<b>Power Consumption</b> 7.4 Kw	<b>Power Consumption</b> 7.4 Kw
<b>Net Weight (Kg)</b> 700	<b>Net Weight (Kg)</b> 785	<b>Net Weight (Kg)</b> 750
<b>Size (H) x (W) x (L)</b> 1650 x 1350 x 1980	<b>Size (H) x (W) x (L)</b> 2080 x 1350 x 2120	<b>Size (H) x (W) x (L)</b> 2040 x 1350 x 1980



## MX 800

Robust design suitable for larger bulk packing applications



Pillow Pack



Gusseted Pack

- As per MX 600 S Pillow Pack
  - Film width upto 800mm
- Heavy duty horizontal and vertical seals




## MX 600 D TWIN PACK

Increased Production Output  
Flexible and Easy to use



Pillow Pack



Gusseted Pack

- As per MX 600 S Pillow Pack
- 1 PLC & HMI Controls 2 machines
  - Can be integrated with 2 separate filling systems



## M05CV HIGH SPEED

Economic High Speed Production  
Produces High Quality Pillow Pouches



Pillow Pack



Gusseted Pack

- As per MX 600 S Pillow Pack
- Rotary Jaw movement for high speed
  - Continuous belt vertical seal
- Will take standard pillow pack forming sets

<b>Bag Type</b> Pillow or Gusseted	<b>Bag Type</b> Pillow or Gusseted	<b>Bag Type</b> Pillow or Gusseted
<b>Max Speed</b> 50 Bags per minute	<b>Max Speed</b> 150 Bags per minute	<b>Max Speed</b> 130 Bags per minute
<b>Bag Width</b> 150 - 380 mm	<b>Bag Width</b> 65mm - 290mm	<b>Bag Width</b> 65mm - 280mm
<b>Bag Length</b> 200 mm - 500 mm	<b>Bag Length</b> 80 mm - 320 mm	<b>Bag Length</b> 80mm - 400mm
<b>Reel Width</b> 325 - 800mm	<b>Reel Width</b> 150 mm - 600 mm	<b>Reel Width</b> 150mm - 600mm
<b>Max Reel Diameter</b> 600 mm	<b>Max Reel Diameter</b> 400mm	<b>Max Reel Diameter</b> 400mm
<b>Power Supply</b> 3PNE 16 AMP	<b>Power Supply</b> 3PNE 16 AMP	<b>Power Supply</b> 3PNE 16 AMP
<b>Air Consumption</b> 216 / 7.7 (Lts per min/ CFM)	<b>Air Consumption</b> 600 / 21.2 (Lts per min/ CFM)	<b>Air Consumption</b> 33 / 1.2 (Lts per min/ CFM)
<b>Power Consumption</b> 7.4 Kw	<b>Power Consumption</b> 10 Kw	<b>Power Consumption</b> 7.4 Kw
<b>Net Weight (Kg)</b> 785	<b>Net Weight (Kg)</b> 1350	<b>Net Weight (Kg)</b> 880
<b>Size (H) x (W) x (L)</b> 2100 x 1645 x 2150	<b>Size (H) x (W) x (L)</b> 1650 x 2700 x 1980	<b>Size (H) x (W) x (L)</b> 1810 x 1450 x 2150